

# ACCESSORIES

## 1/4" NPT GAUGE ISOLATOR VALVE



Model #1075 (MxF)

Model #1050 (FxF)

The Miljoco brass ball valve cock is an ideal isolating valve between a pressure gauge & the medium being measured. The valve is a positive shutoff rated at 600 psi W.O.G., & facilitates the repair or replacement of a gauge without comprising the piped system. CAUTION: A coil syphon should be used between ball valve and steam service.

## 1/4" NPT BRASS NEEDLE VALVE



Model #1100

This sturdy Miljoco brass needle valve, with teflon packing glands, is designed especially for pressure gauge service, and will operate freely up to 2000 psi. The large round knurled handle offers maximum ease and precise control to throttle the pressure on & off to the gauge. CAUTION: A coil syphon should be used between needle valve and steam service.

## 1/4" NPT BRASS SNUBBER



Model #1200

Miljoco porous stone pressure gauge snubbers are designed to dampen pressure pulsations to enhance gauge life. They have no moving parts, thus are completely reliable to 1000 psi. They can be piped together in pairs for certain applications where severe pulsations exist.

## 1/4" NPT STEEL COIL SYPHON



Model #1300

Miljoco coil syphons are required for use with gauges on steam lines, and are designed to form a barrier of water in the coil, preventing steam from attacking the bourdon tube solder joints.

**MILJOCO**  
CORPORATION

14335 E. NINE MILE RD., WARREN, MI 48089 [www.miljoco.com](http://www.miljoco.com) PHONE 586 777-4280 FAX 586 777-7891